

30

OFFICE OF THE PRINCIPAL PATNA COLLEGE

ASHOK RAJ PATH
PATNA UNIVERSITY, PATNA 800005

Website: <https://patnacollege.ac.in>
Phone No: 0612-2678008

EMERGENT NOTICE INVITING QUOTATION

Quotation No: *PC/13*

Date: *09/04/26*

**NAME OF WORK: CONSTRUCTION OF LADIES TOILET FOR THE DEPARTMENT OF
PSYCHOLOGY, PATNA COLLEGE, P.U. PATNA**

Sealed quotations are invited in prescribed format for this work, along with the Earnest Money Deposit, as mentioned in the Terms and Conditions of this notice. For details terms and condition, please visit the office of the undersigned on any working days from 10.30 A.M. to 5.00 P.M. or website of College.

Designation of officer inviting quotation	Principal, Patna College, Patna
Place, Time & Date of receiving of quotation	Office of the Principal, Patna College, Patna up to 3.00 p.m. on 21.04.2026.
Place, Time & Date of opening quotation	Office of the Principal, Patna College, Patna at 3.30 p.m. on 21.04.2026.

PRESCRIBED FORMAT

S.N	Code No	Description	Quantity		Unit	Rate	Amount
						(Rs.)	
1	20.3A.1	Making 25 cm (10") dia bore up to 4 mtr depth below ground with hand auger of approved quality in ordinary soil (vide classification of soil item A) true to plumb and without eccentricity in any stage of operation and disposal of the excavated earth up to 50 mtr, Lead including all lifts, all complete as per approved design and direction of E/I	13	m	m		
2	2.28	Supplying and Filling in plinth with local sand and under floors including, watering, ramming consolidating and dressing complete.	2	Cum	Cum		
3	11.72	Providing designation 100 A one brick flat soiling joints filled with local sand including cost of watering, taxes, royalty all complete as per building specification and direction of E/I,	10	Sqm	Sqm		
4	5.1.2	Providing and laying in position specified grade of reinforced cement concrete excluding the cost of centring, shuttering, finishing and reinforcement-All work up to plinth level- 1:1:5:3(1 cement: 1.5 coarse sand:3 graded stone aggregate 20 mm nominal size)	1.7	Cum	Cum		
5	5.2.2	Reinforced cement concrete work in wall (any thickness), including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts, etc. up to floor five level excluding cost of centring, shuttering, finishing and reinforcement. 1:1:5:3(1 cement: 1.5 coarse sand:3 graded stone aggregate 20mm nominal size)	1.3	Cum	Cum		

22

S.N	Code No	Description	Quantity		Unit	Rate	Amount
						(Rs.)	
6	5.3	Reinforced cement concrete work in beams, suspended floors, roofs having slope upto 15, landings, balconies, shelves, chajjas, lintels, bands, plain window sills, staircases and spiral stair cases upto floor five level excluding the cost of centring, shuttering, finishing and reinforcement with 1:2:4 (1 cement:2 coarse sand:4 graded stone aggregate 20 mm nominal size).	1.3	Cum	Cum		
7	5.33B .4	Add or deduct for providing richer or leaner mixes respectively at all floor levels. Providing M-15 grade R.C.C instead of M-20 grade R.C.C.	1.3	Cum	Cum		
8		Reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete.					
a	5.22.7 A	Thermo-Mechanically Treated bars TMTC-500-8mm dia.	187	Kg	Kg		
b	5.22.1	Mild steel 6.00 mm dia	43	Kg	Kg		
9		Centring and shuttering including strutting, propping etc. and removal of form for.					
a	5.9.1	Foundations, footings, bases of columns etc. for mass concrete.	4	Sqm	Sqm		
b	5.9.6	Columns, Pillars, Piers, Abutments, Posts and Struts	22	Sqm	Sqm		
c	5.9.5	Lintels, beams, plinth bams, griders, bressumers and contilevers.	5	Sqm	Sqm		
d	5.9.3	Suspended floors, roots, landings, balconies and access platform.	5	Sqm	Sqm		
10	6.1.1 4A	Brick work with bricks of class designation 100A in foundations and plinth in : Cement mortar 1 :.6 (1 cement: 6 coarse sand)	1	Cum	Cum		
11	6.18. 4A	Half brick masonry with bricks of class designation 100A in foundations and plinth in : 1 Cement mortar 1:4 (1 cement: 4 coarse send)	37	Sqm	Sqm		
12	6.19A	Extra for half Brick masonry in superstructure above pinth level upto floor V level.	25	Sqm	Sqm		
13	4.1.2	Providing and laying in position cement concrete of specified grade exluding the cost of centring and shuttering-all work upto plinth level. 1:1.5:3	0.70	Cum	Cum		
14	13.24 .2	6 mm cement plaster to ceiling of mix : 1:4(1 cement: 4 coarse sand)	6	Sqm	Sqm		
15	13.11. 2	12 mm cement plaster of mix: 1:4(1 cement :4 coarse sand)	33	Sqm	Sqm		
16	13.36 .2	Extra for providing and mixing water proofing material in proportion recommended by the manufacturers : 12 mm cement plaster 1:4(1 cement :4 sand)	27	Sqm	Sqm		
17	13.12 .2	15 mm cement plaster on rough side of single or half brick wall of mix 1:4(1 cement: 4 coarse sand)	34	Sqm	Sqm		
18	11.39	Providing and laying Ceramic glazed floor tiles 300x300 mm (thickness to be specified by the manufacturer) of 1 st quality conforming to IS : 13755 of NITCO , ORIENT , SOMANY , KAJARIA or equivalent make in colours such as white, Ivory, Grey, Fume , Red , Brown , laid on 20 mm thick cement motar 1:4 (1 cement: 4 Coarse sand) including grouting the joints with white cement and matching pigments etc, complete.	4	Sqm	Sqm		
19	11.36	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS : 15622 (Thickness to be specified by the manufacture) of approved make in all colours, shades except burgundy , bottle green , black of any size as approved by Engineer-in-charge in skirting , risers of steps and dados over 12 mm thick bed of cement Motar 1:3(1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm including pointing in white cement mixed with pigment of matching shade complete.	12	Sqm	Sqm		

pe

S.N	Code No	Description	Quantity		Unit	Rate	Amount
						(Rs.)	
20		Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / aneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) :					
a	21.1.1.1	For fixed portion Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)	4	Kg	Kg		
b	21.1.1.1	For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15	4	Kg	Kg		
21	2631	Providing 4 mm thick A.C.P. of approved quality for proposed aluminium door shutter as per direction of Engineer-in-charge.	1.5	Sqm	sqm		
22	9.100.3	Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete:	2	No	Each		
23	9.97.4	Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868), transparent or dyed to required colour or shade, with necessary screws etc. complete:150x10 mm	4	No	Each		
24	17.1.1.	Providing and fixing water closet squatting pan (Indian type W.C.pan) with 100 mm sand cast Iron P or S trap, 10 litre low fixtures complete. including cutting and making good the walls and level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever) conforming to IS : 7231, with all fittings and floors wherever required :White Vitreous china Orissa pattern W.C. pan of size 580x440 mm with integral type foot rests	1	No	Each		
25	17.7.7	Providing and fixing wash basin with C.I. brackets, 15 mm C.P. brass pillar taps, 32 mm C.P. brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require :White Vitreous China Flat back wash basin size 450x300 mm with single 15 mm C.P. brass pillar tap	2	No	Each		
26	17.8	Providing and fixing white vitreous china pedestal for wash basin completely recessed at the back for the reception of pipes and fittings	2	No	Each		
27	17.28.1.2	Providing and fixing P.V.C. waste pipe for sink or wash basin including P.V.C. waste fittings complete.Semi rigid pipe 40 mm dia	2	No	Each		
28	17.31	Providing and fixing 600x450 mm beveled edge mirror of superior glass (of approved quality) complete with 6 mm thick hard board ground fixed to wooden cleats with C.P. brass screws and washers complete	2	No	Each		

24

S.N	Code No	Description	Quantity		Unit	Rate	Amount
						(Rs.)	
29	17.71	Providing and fixing PTMT liquid soap container 109 mm wide, 125 mm high and 112 mm distance from wall of standard shape with bracket of the same materials with snap fittings of approved quality and colour, weighing not less than 105 gms.	2	No	Each		
30	17.72	Providing and fixing PTMT towel ring trapezoidal shape 215 mm long, 200 mm wide with minimum distances of 37 mm from wall face with concealed fittings arrangement of approved quality and colour, weighing not less than 88 gms.	2	No	Each		
31	18.8.2	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge. Concealed work, including cutting chases and making good the walls etc. 20 mm nominal outer dia Pipes	15	m	m		
32	18.7.3	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge. Internal work - Exposed on wall 25 mm nominal outer dia Pipes	10	m	m		
33	18.9.3	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply including all CPVC plain & brass threaded fittings This includes jointing of pipes & fittings with one step CPVC solvent cement, trenching, refilling & testing of joints complete as per direction of Engineer in Charge. 25 mm nominal outer dia Pipes	20	m	m		
34	18.21.2.1	Providing and fixing unplasticised PVC connection pipe with brass lions :45 cm length 15 mm nominal bore	3	No	Each		
35		Providing and fixing following materials of approved quality, as per direction of Engineer-in-charge.					
a	P.M.R	Two way Bib cock	1	No	Each		
b	P.M.	Health Focet	1	No	Each		
36	18.53	Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931	3	No	Each		
37	18.53 A	Providing and fixing C.P. Brass extension nipple (size 15mmx50mm) of approved make and quality as per direction of Engineer-in-charge.	4	No	Each		
38		Providing and fixing PTMT grating of approved quality and colour					
a	18.58.1.1	Circular type 100 mm nominal dia	2	No	Each		
b	18.58.1.2	125 mm nominal dia with 25 mm waste hole	1	No	Each		
39		Providing and fixing on wall face unplasticised-PVC (working pressure 4 kgf per sqm) rain water pipes conforming to IS :4985 including jointing with seal ring conforming to IS: 5382 leaving 10 mm gap for thermal expansion.					
a	12.78.1	75 mm diameter	10	m	m		

Code No	Description	Quantity		Unit	Rate	Amount
					(Rs.)	
b 12.78 2	110 mm diameter	15	m	m		
40	Providing and fixing on wall face unplasticised -PVC molded fittings/accessories for unplasticised-PVC rain water pipes conforming to (S:4985 including jointing with seal ring conforming to IS: 5382 leaving 10 mm gap for thermal expansion.					
a 12.79 4.1	Single tee without door 75x75x75mm	1	No	Each		
b 12.79 5.1	75 mm bend	4	No	Each		
c 12.79 5.2	110 mm bend	8	No	Each		
41 13.80 A.2	Providing and applying white cement based putty of average thickness 2 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete	61	Sqm	Sqm		
42 13.46 .1	Finishing walls with Acrylic Smooth exterior paint of required shade: New work (Two or more coat applied @ 1.67 ltr/ 10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/ 10 sqm)	61	Sqm	Sqm		
43 9.48 2	Providing and fixing M.S. grills of required pattern in frames of windows etc. with M.S. flats, square or round bars etc. including priming coat with approved steel primer all complete, Fixed to openings/ wooden frames with rawl plugs screws etc	6	Kg	Kg		
44 10.5 1	Providing and fixing 1 mm thick M.S. sheet door with frame of 40x40x6 mm angle iron and 3mm MS gusset plates at the junction and corners all necessary fittings complete including applying a priming coat of approved steel primer-Using M.S. angle 40x40x6 mm for diagonal braces	2	Sqm	Sqm		
45 13.93 .1	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade:Two or more coats on new work	5	Sqm	Sqm		
46 18.65	Providing and fixing PTMT soap Dish Holder having length of 138mm, breadth 102mm, height of 75mm with concealed fitting arrangements, weighing not less than 106 gms	2	No	Each		
47 2.6	Earth work in excavation over areas (exceeding 30 cm in depth. 1.5 m in width as well as 10 sqm on plan) including disposal of excavated earth, lead upto 50 m and lift upto 1.5 m; disposed earth to be levelled and neatly dressed.	4	Cum	Cum		
48 2.8	Earth work in excavation in foundation trenches or drains(not exceeding 1.5 m in width or 10 sqm on plan) including dressing of sides and ramming of bottoms, lift upto 1.5 m . including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m.	1	Cum	Cum		
49 2.26	Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20 cm in depth: consolidating each deposited layer by ramming and watering lead	4	Cum	Cum		
50 6.32 A	Honey- comb brick work 10/11.4 cm thick with bricks of class designation 100A in cement mortar 1:4 (1 cement: 4 coarse sand)	6	Sqm	Sqm		
51 13.17 .1	12 mm cement plaster 1:3(1 cement: 3 coarse sand) finished with a floating coat of neat cement	5	Sqm	Sqm		
52 o362	Providing and filling brick bats of approved quality for proposed soak pit, as per direction of Engineer-in-charge.	1.4	Cum	Cum		

P.L.

S.N.	Code	Description	Quantity		Unit	Rate	Amount	
	No					(Rs.)		
53		Carriage of materials:						
a		Bricks from 8 Km distance of surface road with 1 Km kutcha road from site.	2850	No	%0No			
b		Stone aggregate from 100 Km distance of surface road from Manpur, Gaya.	4.7	Cum	Cum			
c		Sone sand from Koelwar to site, 45 Km distance of surface road.	5.8	Cum	Cum			
d		Local sand from 2Km distance of road and 1 Km distance of kutcha road.	2.6	Cum	Cum			
54		Reserved price for any other unseen work.	1	L.S.	L.S.	4848	4848	
TOTAL								

TERMS & CONDITIONS:

- 1 Earnest Money Deposit in the form of Bank Draft in the favour of Principal, Patna College, Patna or N.S.C./ Time Deposit of Post Office, duly pledged in the name of Principal, Patna College, Patna @ 2% i.e. Rs.4,600/- along with xerox copies of documents related to registration, G.S.T. PAN etc. are essentially required with quotations. Remaining amount of Security Deposits @ 8% of bill amount will be deducted from bill.
- 2 Rate and amount of item vide serial number 54 has been fixed as Rs.4848/- only.
- 3 Work must be completed within 2 month after receiving work order.
- 4 Any registered agency of Government of Bihar / C.P.W.D. /M.E.S. will be considered.
- 5 Payment will be considered after satisfactory completion of work and after submitting satisfactory work completion certificate.
- 6 The undersigned reserve the right to accept or reject any or all the quotations without assigning any reason.
- 7 All disputes, what so ever shall be referred to the sole arbitration of the Principal, Patna College, Patna and his decision shall be final and binding on the agency.


 PRINCIPAL
 PATNA COLLEGE
 PATNA